





Optionales Zubehör: 

- Multifeed-Schienensystem der Premium Serie mit Kurz- oder Langschiene
- Vormastmontage-Halterung (nur für 125 cm Antenne)
- stabile Feedarm Variante (nur für 125 cm Antenne)



Optional accessories: 

- Upgradeable to multifeed rail system of the Premium series with short or long rail
- Back mounting-bracket (only for 125 cm dish)
- stable feed arm (only for 125 cm dish)

**Technische Daten /
technical data**

Modell	125 cm L-Serie	150 cm S-Serie
Farbe Anthrazit (RAL 7011) / Colour anthracite (RAL 7011)	Art.Nr.: S14 EAN: -	- -
Farbe Lichtgrau (RAL 7035) / Colour lightgrey (RAL 7035)	Art.Nr.: S15 EAN: -	S30 -
Farbe Oxidrot (RAL 8012) / Colour oxide red (RAL 8012)	Art.Nr.: - EAN: -	- -
Reflektor Material / Reflector material	Aluminium	
Reflektor Abmessung / Outside dimension	124,5 x 133,5 cm	155,0 x 166,0 cm
Reflektor Wirkfläche / Reflecting dimension	121,0 x 130,0 cm	150,0 x 161,0 cm
Wirkungsgrad / Illumination efficiency	70 %	
Gewinn bei 10.70 GHz / Gain @ 10.70 GHz	41,10 dB	43,00 dB
Gewinn bei 11.70 GHz / Gain @ 11.70 GHz	41,90 dB	43,70 dB
Gewinn bei 12.75 GHz / Gain @ 12.75 GHz	42,60 dB	44,50 dB
F/D Verhältnis / F/D ratio	0,66	
Einstellbereich Elevation / Elevation angle	20° - 50° Vormast 0° - 90°	20° - 90°
Feed-Aufnahme / Feeder clamp	40 / 23 mm	
Mast-Aufnahme / Mast clamp	55 - 100 mm	55 - 100 mm
Reflektorstärke / Reflector thickness	1,5 mm	2,0 mm
Windlast bei 120 km/h / Wind-load @ 120 km/h	162,0 kg	250,0 kg
Gewicht / Weight	15,1 kg	28,8 kg

Gibertini Antenne 125 / 150 cm
Gibertini Antenna 125 / 150 cm

innovative solutions

bauckhage - wiehl